

ANTISLIP RUBBER SPRAY COATING

Preventing Slips, Trips and Falls on Most Surfaces



Anti-Slip coatings, treatments, & compliance specialists



PERFORMANCE FEATURES

- ✓ Interior and exterior use
- ✓ Increases traction and provides cushioning comfort
- ✓ Commercial-grade durability
- ✓ Barefoot and paw friendly
- ✓ Chemical resistant
- ✓ Long-lasting protection

RECOMMENDED APPLICATIONS

- PATIOS, DECKS, OUTDOOR RECREATION AREAS
- LOCKER ROOMS, WATERPARKS, POOL SURROUNDS
- TRAILERS, LOADING DOCKS, AND RAMPS
- BOAT DECKS AND MARINE AREAS
- COMMERCIAL AND RESIDENTIAL USE


COMPLIANCE & CERTIFICATIONS

- Meets NZS 4586:2004 slip resistance requirements (wet pendulum testing)
- VOC-free and non-toxic formulation
- Suitable for barefoot and paw traffic
- Water and chemical resistant

SLIPSAFE NZ – CONSULTATION & SAMPLES

 www.slipsafe.co.nz

 info@slipsafe.co.nz

 0508 754 778

INSTALLATION & APPLICATION METHOD

1. Ensure surface is dry and clean from dust, oil, grease.
2. Prime most surfaces before application; lightly sand if not primed.
3. Stir thoroughly with a drill mixer for 3–5 minutes to evenly distribute rubber particulates.
4. Apply using hopper gun for optimal finish; brush, trowel, squeegee, or roller can also be used.
5. Apply two coats for best performance (25–45 mil dry thickness).
6. Clean equipment immediately after use with water.

COMPATIBLE SURFACES



METAL




WOOD



FIBREGLASS



ALUMINIUM



STEEL



BLACKTOP



CONCRETE

TECHNICAL SPECIFICATIONS

Product Type	Water-based acrylic rubber coating
Colour	Base grey (custom colours available)
Sheen	Textured rubber finish
Compatible Surfaces	Metal, wood, fibreglass, aluminium, steel, blacktop, and concrete
Coverage	2.8–4.2 m ² (2 coats sprayed) per 3.78 litres, depending on substrate
Application Temperature	Above 7°C (45°F)
Touch Dry	1 hour
Full Cure	5–8 hours, Full strength: 4–7 days
Recoat Time	2–3 hours between coats
Water Resistant	Yes, but not for continuous submersion
Chemical Resistant	Yes
Shelf Life	5 years
Treatment Life	3–12 months (depending on surface and traffic)
Storage	Store between 10°C–27°C. Protect from freezing
Expected Service Life	2+ years under normal wear
Maintenance	Surface can be cleaned by power washing or scrubbing with a deck brush and rinsing thoroughly. Compatible with most floor cleaners.
Warranty	2 years against loss of slip resistance (conditions apply)