ANTISLIP POLISH GRIP
Penetrating Sealer

SlipSafe
Anti-Slip coatings, treatments, & compliance specialists

PERFORMANCE FEATURES

- Increases traction on polished and natural surfaces
- Protects against water and stains
- Maintains original colour and shine
- Easy application and maintenance
- Safe for use in food preparation areas

RECOMMENDED APPLICATIONS

HOTELS, MOTELS, AND RESORTS

SENIOR LIVING FACILITIES

RESTAURANTS

KITCHENS AND BATHROOMS

PATIOS, HIGHLY POLISHED STONE SURFACES

COMPLIANCE & CERTIFICATIONS

Meets NZS 4586:2004 slip resistance requirements (wet pendulum testing)

VOC-free and non-toxic formulation

Suitable for interior and exterior use

Water, stain, and weather resistant

SLIPSAFE NZ – CONSULTATION & SAMPLES

www.slipsafe.co.nz info@slipsafe.co.nz 0508 754 778

ANTISLIP POLISH GRIP
Penetrating Sealer

SlipSafe
Anti-Slip coatings, treatments, & compliance specialists

INSTALLATION & APPLICATION METHOD

1. Clean surface thoroughly with a pH-neutral cleaner and ensure completely dry.
2. Test in an inconspicuous area before full application.
3. Do not thin or dilute. Apply evenly using a clean white towel, microfiber towel, or Polish Grip Applicator.
4. Allow product to penetrate for 3–5 minutes.
5. Remove all excess product before it dries using a clean towel or carpet bonnet.
6. For a second application, wait at least 1 hour before reapplying.
7. Full cure achieved in 24–72 hours (depending on conditions)

COMPATIBLE SURFACES

TECHNICAL SPECIFICATIONS

Product Type	Professional-grade penetrating sealer
Colour	Clear
Finish	Invisible – retains natural surface shine
Compatible Surfaces	Granite, marble, natural stone, porcelain tile, concrete, ceramic tile, slate, limestone, grout, terrazzo, travertine, glazed tile, quarry tile
Coverage	Up to 27.9 m² per 473 mL (pint) | Up to 223 m² per 3.78 litres (gallon)
Dry to Touch	Immediately after treatment
Light Traffic	4-6 hours
Full Cure	Up to 72 hours
Recoat Time	1 hour
Water Resistant	Yes
Stain Resistant	Yes
Shelf Life	1 year
Treatment Life	3-12 months (depending on surface and traffic)
Storage	Store tightly sealed at ~25°C
Expected Service Life	6–12 months depending on foot traffic and surface type
Maintenance	Clean treated surfaces with a pH-neutral cleaner to maintain performance. Reapply as needed to maintain slip resistance and protection

SLIPSAFE NZ – CONSULTATION & SAMPLES
www.slipsafe.co.nz info@slipsafe.co.nz 0508 754 778